

2023 CHEVROLET COLORADO PRELIMINARY SPECIFICATIONS

ENGINE

| Type: | 2.7L I-4 Turbo DOHC VVT DI with Active Fuel Management and Stop/Start |
|-----------------------------|--|
| Bore & Stroke (in. / mm): | 3.63 x 4.01 / 92.25 x 102 |
| Block Material: | Cast aluminum |
| Cylinder Head Material: | Cast aluminum |
| Valvetrain: | Dual-overhead camshafts, four-valves per cylinder, tripower valvetrain with continuously variable valve timing, variable valve lift and Active Fuel Management |
| Fuel Delivery: | Direct high-pressure fuel injection with Active Fuel Management |
| Horsepower (hp / kW @ rpm): | Base: 237 / 177 @ 5600 (GM est.) – standard Mid & High: 310 / 231 @ 5600 (GM est.) – available |
| Torque (lb-ft / Nm @ rpm): | Base: 259 / 352 @ 5600 (GM est.) – standard Mid: 390 / 530 @ 3000 (GM est.) – available High: 430 / 569 @ 3000 (GM est.) – available |

TRANSMISSION & AXLE

| Type: | Hydra-Matic 8L90 eight-speed automatic |
|--------------------|--|
| Gear Ratios (:1) | |
| First: | 4.56 |
| Second: | 2.97 |
| Third: | 2.08 |
| Fourth: | 1.69 |
| Fifth: | 1.27 |
| Sixth: | 1.00 |
| Seventh: | 0.85 |
| Eighth: | 0.65 |
| Reverse: | 4.56 |
| Final Drive Ratio: | 3.42 |

CHASSIS & SUSPENSION

| 0117 (0010 & 0001 E1101011 | |
|----------------------------|---|
| Front Suspension: | 2WD and 4WD: independent coil-over-shock; twin-tube |
| | shocks; Multimatic DSSV dampers on ZR2 |
| Rear Suspension: | Solid axle with semi-elliptic two-stage multi-leaf |
| | springs; twin-tube shocks; Multimatic DSSV dampers |
| | on ZR2 |
| Rear axle: | Open differential (std. WT and LT) |
| | G80 limited-slip differential (std. Trail Boss & Z71) |
| | Power-locking front and rear differentials (std. ZR2) |
| Steering Type: | Electric power-assisted rack-and-pinion |
| Brake Type: | Power-assisted four-wheel discs with Duralife™ long- |
| | life brake rotors; standard ABS; hill descent control |
| | available (std. Trail Boss & Z71) |



| Brake Rotor Size (in / mm): | 13.4 / 340 (front) |
|-----------------------------|---|
| | 13.3 / 337 (rear) |
| Wheel Size: | 17 x 8-in. steel (std. WT) |
| | 17 x 8-in. aluminum (std. LT) |
| | 17 x 8-in. aluminum (std. ZR2) |
| | 18 x 8.5-in. aluminum (std. Trail Boss & Z71) |
| Tire Size: | P255/65R17 all-season (WT) |
| | P255/55R20 all-season (Z71) |
| | P285/70R17 mud/terrain (ZR2) |
| | P265/65R18 all-terrain (Trail Boss & Z71) |

EXTERIOR DIMENSIONS

| EXTERIOR DIMENSIONS | |
|-----------------------------------|--------------------------------|
| Wheelbase (in. / mm): | 131.4 / 3337 |
| Overall Length (in. / mm): | 213 / 5411 – WT & LT & Z71 |
| | 213.2 / 5416 – Trail Boss |
| | 212.7 / 5402 – ZR2 |
| Overall Width (in. / mm): | 84.4 / 2144 – WT & LT |
| | 84.4 / 2144 – Trail Boss & Z71 |
| | 84.4 / 2144 – ZR2 |
| Overall Height (in. / mm): | 78.8 / 2001 – WT, LT |
| | 79.6 / 2021 – Z71 |
| | 79.9 / 2029 – Trail Boss |
| | 81.9 / 2078 – ZR2 |
| Track – front (in. / mm): | 62.8 / 1594 – WT, LT |
| | 62.6 / 1590 – Z71 |
| | 66.2 / 1679 – Trail Boss |
| | 66.3 / 1684 – ZR2 |
| Track – rear (in. / mm): | 62.6 / 1590 – Z71 |
| | 62.8 / 1594 – WT, LT |
| | 66.1 / 1679 – Trail Boss |
| | 66.3 / 1684 – ZR2 |
| Ground Clearance (in. / mm): | 7.9 / 200 – WT, LT |
| | 8.9 / 227 – Z71 |
| | 9.5 / 242 – Trail Boss |
| | 10.7 / 272 – ZR2 |
| Off- road Approach Angle (deg.): | 29.1 – Z71 |
| | 30.5 – Trail Boss |
| | 38.3 – ZR2 |
| Off-road Departure Angle (deg.): | 22.3 – Z71 |
| | 22.4 – Trail Boss |
| | 25.1 – ZR2 |
| Off-road Break-Over Angle (deg.): | 19.5 – Z71 |
| | 21 – Trail Boss |
| | 24.6 – ZR2 |

INTERIOR DIMENSIONS

| Headroom (in. / mm): | 40.3 / 1023 (front) |
|----------------------|---------------------|
| | 38.3 / 972 (rear) |



| Legroom (in. / mm): | 45.2 /1147 (front) |
|---------------------------|---------------------|
| | 34.7 / 881 (rear) |
| Shoulder Room (in. / mm): | 57.4 /1390 (front) |
| , , | 56.1 / 1426 (rear) |
| Hip Room (in. / mm): | 54.7 / 1390 (front) |
| , , | 53.1 / 1348 (rear) |

FUEL TANK CAPACITY (approx.)

21.3 gal. / 80.6 liters

CURB WEIGHT, CAPACITIES & TRAIL FRING

| CORD WEIGHT, CAI ACHTEC & IT | V. 11 = 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
|--|---|
| Curb Weight (lb. / kg): | 4716 / 2139 – WT & LT |
| | 4971 / 2255 – Trail Boss & Z71 |
| | 5298 / 2403 – ZR2 |
| GVWR (lb. / kg) ¹ : | 6250 / 2835 – WT & LT |
| | 6250 / 2835 – Trail Boss & Z71 |
| | 6200 / 2812 – ZR2 |
| Max Payload (lb. / kg) ² : | 1684 / 764 – WT & LT |
| | 1587 / 720 – Trail Boss & Z71 |
| | 1151 / 522 – ZR2 |
| Max Trailering (lb. / kg) ³ : | 7700 / 3493 – WT & LT (available) |
| | 7700 / 3493 – Trail Boss & Z71 |
| | 6000 / 2722 – ZR2 |

When properly equipped; includes weight of vehicle, passengers, cargo and equipment.

²For comparison purposes only. See the owner's manual and the label on the vehicle door jamb for the carrying capacity of a specific vehicle.

³Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The

weight of passengers, cargo and options or accessories may reduce the amount you can tow.