04/2022 Page 1

Technical specifications. BMW 7 Series. i7 xDrive60.



		BMW i7 xDrive60
Vehicle Category		Dettem alestris retists (DEVA / Co. L.)
Drive type / body style		Battery electric vehicle (BEV) / Sedan
Body		
No. of doors / seats		4/5
Length/width/height (unladen)	mm	5391 / 1950 / 1544
Wheelbase	mm	3215
Track, front/rear	mm	1714 / 1735
Turning circle Turning circle with Integral Active Ste	m eerina m	13.1 12.3
Ground clearance (unladen)	mm	136
Weight, unladen (DIN/EU)	kg	2640 / 2715
Max. load to DIN	kg	610
Max. permissible weight	kg	3250
Max. axle load, front/rear	kg	1550 / 1810
Max. trailer load,		2000 (750
braked (12%)/unbraked Max. roofload/towbar download	kg	2000 / 750 / 80
Luggage comp. capacity	kg I	500
Air resistance	c _x x A	0.24 x 2.60
- III resistance	<u> </u>	012 1 X 2100
Power Unit		
Drive concept		Electric all-wheel drive, drive torque sent by one electric motor to
		the front wheels and one to the rear wheels, as required, in a
May gyatam autorit	Lat	coordinated process
Max. system output	kW/hp Nm	400 / 544
Max. system torque System power-to-weight ratio	kg/kW	6.6
Type of transmission	Ng/ NV	Automatic transmission, single-stage with fixed ratio
7,500		
Electric Motors		
Motor technology		Fifth-generation BMW eDrive technology:
		electrically excited synchronous motors, power electronics and
		transmission sharing the same housing, generator function for recuperating energy
Front Electric Motor		recoperating energy
Peak output to ECE R 85	kW/hp	190 / 258
at	rpm	8000
Continuous output to ECE R 85	kW/hp	70 / 95
Max. torque	Nm	365
at	rpm	0 – 5000
Gear ratio	:1	8.770
Rear Electric Motor	k\M/hn	230 / 313
Peak output to ECE R 85	kW/hp rpm	8000
Continuous output to ECE R 85	kW/at	95 / 129
Max. torque	Nm	380
at	rpm	0 – 6000
Gear ratio	:1	9.400
High-voltage Battery		1912
Storage technology		Lithium-ion
Installation Voltage	V	<u>Underfloor</u> 376.4
Battery capacity	v Ah	280.8
Energy capacity, net	kWh	101.7
Charging time, 10 – 100% charge		< 5.5 hours at 22 kW (32 A / 380 V, three-phase AC, Wallbox)
Charging time, 10 – 80% charge		34 min. at 195 kW (DC, fast-charging station)
Charging Unit		0 11 10 1 11 12 20 10 11 11 11 11 11
Type		Combined Charging Unit (CCU) with built-in 4 kW voltage
Max. charging rate		transformer for supplying power to the 12V electrical system
AC, single-phase	kW	3.7 (EU) / 7.4 (incl. CN, KR) / 11.0 (US, JP)
Max. charging rate	1377	5 (25) (5.4) (4.4) · . (10 (65)).)
AC, three-phase	kW	22.0
Max. charging rate		
DC	kW	195

		BMW i7 xDrive60					
Driving Dynamics and Safety							
Suspension, front		Double-wishbone axle in aluminium construction, adaptive air					
	S	suspension with automatic self-levelling, electronically controlled					
		dampers					
Suspension, rear	F	ive-link axle in aluminium construction, adaptive air suspension					
		with automatic self-levelling, electronically controlled dampers					
Brakes, front		Vented disc brakes, with four-piston fixed callipers					
Brakes, rear		Vented disc brakes, with single-piston floating callipers					
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction					
- , ,		Control), ARB technology (near-actuator wheel slip limitation),					
		CBC (Cornering Brake Control), DBC (Dynamic Brake Control),					
		Dry Braking function, fading compensation, drive-off assistant,					
		trailer stability control, Performance Control;					
		optional: active roll stabilisation					
Safety equipment	9	Standard: airbags for driver and front passenger, side airbags for					
	C	driver and front passenger, head airbags for front and rear seats,					
		three-point inertia-reel seatbelts on all seats with belt stopper,					
		belt tensioner and belt force limiter in the front, crash sensors,					
		tyre pressure indicator					
Steering		Electric Power Steering (EPS)					
_		with Servotronic function and variable steering ratio;					
		optional: Integral Active Steering					
Steering ratio, overall	:1	15.6					
Tyres, front/rear		245/50 R19 105Y XL					
Rims, front/rear		8.5J x 19 light-alloy					
Performance							
Acceleration 0–100 km/h	S	4,7					
Top speed	km/h	240 (electronically limited)					
Flackia Dania Carannakia /							
Electric Power Consumption /							
Range							
Electric power consumption	LAME /100 !	10 (10 (
combined (WLTP)	kWh/100 km	19.6 – 18.4					
Electric power consumption	MAIN /1 00 I						
combined (NEDC)	kWh/100 km	- - -					
Range (WLTP)	km	591 – 625					
Environmental Characteristics							
Emission rating		Electric vehicle					

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) All figures relating to performance, fuel/electric power consumption and emissions are provisional.

The fuel consumption, CO_2 emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2.

04/2022 Page 3

BMW 7 Series. 735i.

(Not available in Europe)

		BMW 735i
		DIMM /221
Body		
No. of doors / seats		4/5
Length/width/height (unladen)	mm	5391 / 1950 / 1544
Wheelbase	mm	3215
Track, front/rear	mm	1713 / 1736
Turning circle	m	12.9
Fuel tank capacity Engine oil 1)	approx. l	74 3)
Weight, unladen, to DIN/EU		2075 / 2150
Max. load to DIN	kg kg	710
Max. permissible weight	kg kg	2785
Max. axle load, front/rear	kg kg	1325 / 1510
Max. trailer load	- Kg	13237 1310
braked (12%)/unbraked	kg	-/-
Max. roofload/towbar download	kg	-/-
Luggage comp. capacity		540
Air resistance	cx x A	0.26 x 2.59
Power Unit		
Engine technology		BMW TwinPower Turbo technology: turbocharger, High Precision
		Injection, VALVETRONIC fully variable valve timing, Double-VANOS
		variable camshaft timing, $48V$ mild hybrid technology using an electric
		motor integrated into the transmission
Max. output, overall 2)	kW/hp	210 / 286
Max. torque, overall 2)	Nm	425
Petrol Engine		
Config./No. of cyls./valves		In-line / 6 / 4
Effective capacity	СС	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		Min. RON 91
Nominal power	kW/hp	200 / 272
at	rpm	5000 – 6500
Nominal torque	Nm	400
at	rpm	1750 – 4500
Output per litre	kW/l	66.7
Electric Motor		
Nominal power	kW/hp	13 / 18
Nominal torque	Nm	200
Nominartorque	INIII	200
Electrical System		
12V battery/installation	Ah/-	70 / engine compartment
48V battery/installation	Ah/-	20 / Jugagge compartment
10 V Batter y/mstanation	7 (11)	20 / loggage comparantent
Driving Dynamics and Safety		
Suspension, front		Double-wishbone axle in aluminium construction, adaptive air suspension with automatic self-levelling, electronically controlled
Cuananalan vaa-		dampers
Suspension, rear		Five-link axle in aluminium construction, adaptive air suspension with
Brakes, front		automatic self-levelling, electronically controlled dampers Vented disc brakes, with four-piston fixed callipers
		Vented disc brakes, with single-piston floating callipers Vented disc brakes, with single-piston floating callipers
Brakes, rear Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
Driving stability systems		ARB technology (near-actuator wheel slip limitation), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, fading compensation, drive-off assistant, Performance Control; optional: active roll stabilisation
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt stopper, belt tensioner and belt force limiter in the front, crash sensors, tyre pressure indicator
Steering		with Servotronic function and variable steering ratio; optional: Integral Active Steering
Steering ratio, overall	:1	15.4
Tyres, front/rear		245/50 R19 105Y XL
Rims, front/rear		8.5J x 19 light-alloy

04/2022 Page 4

		DMM 725'		
		BMW 735i		
Transmission				
Type of transmission		Eight-speed Steptronic transmission		
Performance				
Power-to-weight ratio (DIN)	kg/kW	9.9		
Acceleration 0–100 km/h	S	6.7		
Top speed	km/h	250		
BMW EfficientDynamics				
BMW EfficientDynamics		48V mild hybrid technology, Brake Energy Regeneration with		
standard features	rec	recuperation display, Auto Start Stop function, Personal and Efficient		
	mode	e with coasting function, Proactive Driving Assistant, Optimum Shift		
	Indic	ator, Electric Power Steering, BMW EfficientLightweight, optimised		
	aero	dynamic attributes, active air flap control, on-demand operation of		
	ar	ncillary units, map-regulated oil pump, differential with optimised		
		warm-up behaviour, tyres with reduced rolling resistance		
Fuel Consumption ECE				
Combined (WLTP)	1/100	7.9		
CO ₂ (WLTP)	g/km	182		
Combined (NEDC)	I/100	<u>- </u>		
CO ₂ (NEDC)	g/km			
Emission rating		Euro 6d		

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) All figures relating to performance, fuel/electric power consumption and emissions are provisional.

The fuel consumption, CO_2 emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2.

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)

³⁾ Figures not yet available

04/2022 Page 5

BMW 7 Series. 740i.

(Not available in Europe)

		BMW 740i
Body		
No. of doors / seats		4/5
Length/width/height (unladen)	mm	5391 / 1950 / 1544
Wheelbase	mm	3215
Track, front/rear	mm	1713 / 1736
Turning circle	m	12.9
Fuel tank capacity	approx. I	74
Engine oil 1)	I	3)
Weight, unladen, to DIN/EU	kg	2090 / 2165
Max. load to DIN	kg	695
Max. permissible weight	kg	2785
Max. axle load, front/rear	kg	1340 / 1510
Max. trailer load		
braked (12%)/unbraked	kg	2100 / 750
Max. roofload/towbar download	kg	_/85
Luggage comp. capacity	1	540
Air resistance	cx x A	0.26 x 2.59
Dawe Hait		
Power Unit Engine technology		BMW TwinPower Turbo technology: turbocharger, High Precision
Engine technology		Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshoft timing, 48V mild hybrid technology using an electric motor integrated into the transmission
Max. output, overall 2)	kW/hp	280 / 380
Max. torque, overall 2)	Nm	540
Petrol Engine		
Config./No. of cyls./valves		In-line / 6 / 4
Effective capacity	СС	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		Min. RON 91
Nominal power	kW/hp	280 / 380
at	rpm	5200 – 6250
Nominal torque	Nm	520
at Output per litre	rpm kW/l	1850 – 5000 93.4
Output per litre	KVV/1	JJ.4
Electric Motor		
Nominal power	kW/hp	13 / 18
Nominal torque	Nm	200
Electrical System		
12V battery/installation	Ah/-	70 / engine compartment
48V battery/installation	Ah/-	20 / luggage compartment
Driving Dynamics and Safety		
Suspension, front		Double-wishbone axle in aluminium construction, adaptive air suspension with automatic self-levelling, electronically controlled dampers
Suspension, rear		Five-link axle in aluminium construction, adaptive air suspension with automatic self-levelling, electronically controlled dampers
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
		ARB technology (near-actuator wheel slip limitation), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, fading compensation, drive-off assistant, trailer stability control, Performance Control; optional: active roll stabilisation
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver
		and front passenger, head airbags for front and rear seats, three-point
		inertia-reel seatbelts on all seats with belt stopper, belt tensioner and
		belt force limiter in the front, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS)
		with Servotronic function and variable steering ratio;
Chaoring ratio overall	.1	optional: Integral Active Steering 15.4
Steering ratio, overall Tyres, front/rear	:1	245/50 R19 105Y XL
Rims, front/rear		8.5J x 19 light-alloy
inno, noncrea		U.J.A. I.J. light-unuy

04/2022 Page 6

			DM:/ 7 (0)
			BMW 740i
Transmission			
Type of transm	ission		Eight-speed Steptronic transmission
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	7.5
Acceleration	0-100 km/h	S	5.4
Top speed		km/h	250
BMW Efficient	Dynamics		
BMW Efficient	Dynamics		48V mild hybrid technology, Brake Energy Regeneration with
standard features		m	recuperation display, Auto Start Stop function, Personal and Efficient node with coasting function, Proactive Driving Assistant, Optimum Shift ndicator, Electric Power Steering, BMW EfficientLightweight, optimised
			perodynamic attributes, active air flap control, on-demand operation of
			ancillary units, map-regulated oil pump, differential with optimised
			warm-up behaviour, tyres with reduced rolling resistance
Fuel Consumpt	tion ECE		
Combined (WL		1/100	8.0 – 7.0
CO ₂ (WLTP)	•	g/km	183 – 159
Combined (NEI	DC)	1/100	-
CO ₂ (NEDC)		g/km	
Emission rating	1		Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) All figures relating to performance, fuel/electric power consumption and emissions are provisional.

The fuel consumption, CO_2 emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO_2 emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO_2 -Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO_2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2.

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)

³⁾ Figures not yet available

04/2022 Page 7

BMW 7 Series. 760i xDrive. (Not available in Europe)

		BMW 760i xDrive
Body		
No. of doors / seats		4/5
Length/width/height (unladen)	mm	5391 / 1950 / 1544
Wheelbase	mm	3215
Track, front/rear	mm	1714 / 1736
Turning circle	m	12.9
Fuel tank capacity	approx. I	74
Engine oil 1)	1	3)
Weight, unladen, to DIN/EU	kg	2270 / 2345
Max. load to DIN	kg	710
Max. permissible weight	kg	2980
Max. axle load, front/rear	kg	1470 / 1565
Max. trailer load		
braked (12%)/unbraked	kg	-/-
Max. roofload/towbar download	d kg	-/-
Luggage comp. capacity	I	540
Air resistance	cx x A	0.26 x 2.59

Power Unit

Rims, front/rear

Power Unit				
Engine technology		TwinPower Turbo technology with cross-bank exhaust manifold: two twin-scroll turbochargers, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing, 48V mild hybrid technology using an electric motor integrated into the		
		transmission		
Max. output, overall 2)	kW/hp	400 / 544		
Max. torque, overall 2)	Nm	750		
Petrol Engine				
Config./No. of cyls./valves		V/8/4		
Effective capacity	СС	4395		
Stroke/bore	mm	88.3 / 89.0		
Compression ratio	:1	11.0		
Fuel		Min. RON 91		
Nominal power	kW/hp			
at	rpm			
Nominal torque	Nm			
at	rpm			
Output per litre	kW/l			
	KW71	31.0		
Electric Motor	13.77	12.110		
Nominal power	kW/hp			
Nominal torque	Nm	200		
Electrical System				
12V battery/installation	Ah/-			
48V battery/installation	Ah/-	20 / luggage compartment		
Driving Dynamics and Safety				
Suspension, front	Double-wishbone axle in aluminium construction, adaptive air suspension with automatic self-levelling, electronically controlled dampers			
Suspension, rear	Five-link axle in aluminium construction, adaptive air suspension with automatic self-levelling, electronically controlled dampers			
Brakes, front		Vented disc brakes, with four-piston fixed callipers		
Brakes, rear		Vented disc brakes, with single-piston floating callipers		
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),		
<i>,</i> ,	ARB technology (near-actuator wheel slip limitation), CBC (Cornering			
		Brake Control), DBC (Dynamic Brake Control), Dry Braking function,		
		fading compensation, drive-off assistant, DSC networked with xDrive		
	all-wheel-drive system, Performance Control; optional: active roll			
		stabilisation		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for drive		
		and front passenger, head airbags for front and rear seats, three-point		
		inertia-reel seatbelts on all seats with belt stopper, belt tensioner and		
		belt force limiter in the front, crash sensors, tyre pressure indicator		
Steering		Electric Power Steering (EPS) with Servotronic function and variable		
_		steering ratio; optional: Integral Active Steering		
Steering ratio, overall	:1			
Tyres, front/rear		255/45 R20 105Y XL / 285/40 R20 108Y XL		
Rims front/rear		91 x 20 light-alloy / 10 51 x 20 light-alloy		

 $9J \times 20$ light-alloy / $10.5J \times 20$ light-alloy

04/2022 Page 8

			BMW 760i xDrive	
Transmission				
Type of transmi	ission		Eight-speed Steptronic transmission	
Performance				
Power-to-weigh	ht ratio (DIN)	kg/kW	5.7	
Acceleration	0-100 km/h	S	4.2	
Top speed		km/h	250	
BMW Efficient	Dynamics			
BMW EfficientD	BMW EfficientDynamics 48V mild hybrid technology, Brake Energy Regeneration wi		48V mild hybrid technology, Brake Energy Regeneration with	
standard featur	es	recuperation display, Auto Start Stop function, Personal and Efficient		
			ode with coasting function, Proactive Driving Assistant, Optimum Shift	
			dicator, Electric Power Steering, BMW EfficientLightweight, optimised	
			erodynamic attributes, active air flap control, on-demand operation of	
			ncillary units, map-regulated oil pump, efficiency-optimised all-wheel	
		dri	ve, differential with optimised warm-up behaviour, tyres with reduced	
			rolling resistance	
Fuel Consumpt	ion ECE			
Combined (WLT	ΓP)	1/100	11.2	
CO ₂ (WLTP)		g/km	255	
Combined (NED	OC)	1/100		
CO ₂ (NEDC)		g/km	-	
Emission rating			Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) All figures relating to performance, fuel/electric power consumption and emissions are provisional.

The fuel consumption, CO_2 emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2.

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)

³⁾ Figures not yet available

04/2022 Page 9

Exterior and interior dimensions.

BMW 7 Series. i7 xDrive60.







