

## Technical specifications

	2.0 Diesel 140 HP FWD 16v	2.0 Diesel 170 HP FWD 16v	2.0 Diesel 170 HP AWD 16v	2.4 Petrol 170 HP FWD 16v*	3.6 Petrol 280 HP AWD 24v
<b>Engine</b>					
No. of cylinders, arrangement	4, in line	4, in line	4, in line	4, in line	V6
Bore × stroke (mm)	83 x 90.4	83 x 90.4	83 x 90.4	88 x 97	96 x 83
Displacement (cm <sup>3</sup> )	1956	1956	1956	2360	3605
Emissions level	Euro 5+	Euro 5+	Euro 5+	Euro 6	Euro 6
Compression ratio	16.5	16.5	16.5	10.5	10.2
EC max. power: kW (HP) at rpm	103 kW (140 HP) @ 4500 rpm	125 kW (170 HP) @ 4000 rpm	125 kW (170 HP) @ 4000 rpm	125 kW (170 HP) @ 6000 rpm	206 kW (280 HP) @ 6350 rpm
EC max. torque: Nm at rpm	350 @ 1750 - 2000 rpm	350 @ 1750 - 2500 rpm	350 @ 1750 - 2500 rpm	220 @ 4500 rpm	342 @ 4350 rpm
Supply	Direct injection Common Rail Multijet 2	Direct injection Common Rail Multijet 2	Direct injection Common Rail Multijet 2	Sequential, multiport, electronic and returnless	Multiport fuel injection
<b>Transmission</b>					
Drive type	FWD	FWD	AWD	FWD	AWD
Gearbox type	Manual	Manual	Automatic	Automatic	Automatic
Number of speeds	6	6	6	6	6
Steering	Hydraulic rack and pinion				
Turning circle/ min. kerb-to-kerb (m)	11.6				
<b>Brakes</b>					
<b>Brakes (disc)</b>					
Front: Ø mm	330 × 28 (ventilated)	330 × 28 (ventilated)	330 × 28 (ventilated)	330 × 28 (ventilated)	330 × 28 (ventilated)
Rear: Ø mm	328 × 12	328 × 12	328 × 12	328 × 12	328 × 12
<b>Suspension</b>					
Front	Independent, MacPherson type with anti-roll bar				
Rear	Independent, Multilink type with wishbones, anti-roll bar, coil springs and telescopic shock absorbers				
<b>Dimensions</b>					
Wheelbase (mm)	2890	2890	2890	2890	2890
Length / width (mm)	4910 (Cross 4924) / 1878	4910 (Cross 4924) / 1878	4910 (Cross 4924) / 1878	4910 / 1878	4910 / 1878
Height (mm) - with roof rails	1705	1705	1705	1705	1705
Front / rear track (mm)	1571 / 1582	1571 / 1582	1571 / 1582	1571 / 1582	1571 / 1582
Front / rear overhang (mm)	1005 / 1015	1005 / 1015	1005 / 1015	1005 / 1015	1005 / 1015
Luggage compartment volume (dm <sup>3</sup> )	7-seater configuration: 145 (to belt) 5-seater configuration: 540 (to belt) 2-seater configuration: 1461 (to roof)				

<b>Wheels</b>					
Tyres	225/65R17	225/65R17	225/65R17	225/65R17	225/65R17
	225/55R19	225/55R19	225/55R19	225/55R19	225/55R19
<b>Weights - Capacities</b>					
Unladen weight (kg)	1865	1865	2014	1812	1956
Kerb weight (kg)	1940	1940	2089	1887	2031
Max. towable weight, braked (kg)	1250	1250	1100	454	1100
Max. towable weight, non-braked (kg)	450	450	450	450	450
Fuel tank (litres)	77.6	77.6	80.0	77.6	80.0
<b>Performance</b>					
Top speed (km/h)	185	197	183	182	208
Acceleration (s) 0-100 km/h	12.3	11.0	11.1	13.3	8.4
<b>Fuel consumption (l/100 km)</b>					
Urban / extra-urban / combined cycle	8.3 / 5.3 / 6.4	8.3 / 5.3 / 6.4	9.6 / 6.0 / 7.3	13.3 / 7.5 / 9.6	15.9 / 8.5 / 11.3
CO <sub>2</sub> (g/km)	169	169	194	225	262

- Engine not available in Italy