**Technical specifications.** The new BMW 6 Series Gran Turismo. 630i.



		DMW 620j Gran Turiana
		BMW 630i Gran Turismo
Body		
No of doors/seats		5/5
Length/width/height 1)	mm	5091 / 1902 / 1538
(unladen)		
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1649
Ground clearance	mm	138
Turning circle	m	12.3
Fuel tank capacity	approx. I	68
Engine oil <sup>2)</sup>		5.25
Weight, unladen, to DIN/EU	kg	1785 / 1860
Max load to DIN	kg	665
Max permissible weight	kg	2450
Max axle load, front/rear	kg	1230 / 1380
Max trailer load,	kg	0100/750
braked (12%)/unbraked		2100/750
Max roofload/max towbar download	kg	75 / 100
Luggage comp capacity	1	600 – 1800
Air resistance	Cd X A	0.25 x 2.54
All Tesistance	Ud X A	0.23 \ 2.34
Power Unit		
Config/No of cyls/valves		In-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: twin-scroll turbocharger, High Precision
		Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable
		camshaft timing
Effective capacity	CC	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	10.2
Fuel		Min. RON 91
Max output	kW/hp	190 / 258
at	rpm	5000 – 6500
Max torque	Nm	400
at	rpm	1550 – 4400
48V mild hybrid technology		
Max output	kW/hp	8/11
Electrical System	A  - /	00 / human and and the set
12V battery/installation	Ah/-	90 / luggage compartment
48V battery/installation	Ah/-	11 / engine compartment
Driving Dynamics and Safe		
Suspension, front		Double-wishbone axle in aluminium construction with separate lower track arm
Suspension, none		small steering roll radius, transverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air
		suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
		Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
		Fading Compensation, Start-Off Assistant; optional: Adaptive suspension,
		Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
<u></u>		crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS),
		optional: Integral Active Steering
Steering ratio, overall	:1	17.0
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy

		BMW 630i Gran Turismo
Transmission		
Type of transmission		Eight-speed Steptronic transmission
Gear ratios	I :1	5.250
	II :1	3.360
	III :1	2.172
	IV :1	1.720
	V :1	1.136
	VI :1	1.000
	VII :1	0.823
	VIII :1	0.640
	R :1	3.712
Final drive	:1	3.077
Performance		
Power-to-weight ratio (DIN)	kg/kW	9.4
Output per litre	kW/I	95.1
Acceleration 0–100 km	/h s	6.5
Top speed	km/h	250
BMW EfficientDynamics		
BMW EfficientDynamics standard features		Mild hybrid technology with 48V starter-generator, Brake Energy Regeneratio with recuperation display, Auto Start Stop function, ECO PRO and COMFOR mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance
Fuel Consumption ECE Urban	l/100 km	7.4 – 7.2
Extra-urban	l/100 km	5.4 - 5.2
Combined	l/100 km	6.1 – 5.9
CO <sub>2</sub>	g/km	139 – 135

Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Height including roof fin
 Oil change

Emission rating

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

## The new BMW 6 Series Gran Turismo. 640i.

		BMW 640i Gran Turismo
Body		
No of doors/seats		5/5
Length/width/height 1)	mm	5091 / 1902 / 1538
(unladen)		0070
Wheelbase	mm	3070
Track, front/rear	mm	1615/1649
Ground clearance	mm	138
Turning circle	m	12.3
Fuel tank capacity	approx. I	68
Engine oil 2)		6.5
Weight, unladen, to DIN/EU	kg	1855/1930
Max load to DIN	kg	655
Max permissible weight	kg	2510
Max axle load, front/rear	kg	1190 / 1400
Max trailer load,	kg	0400 / 750
braked (12%)/unbraked		2100/750
Max roofload/max towbar	kg	75 / 100
download		600 1000
Luggage comp capacity		600 - 1800
Air resistance	C <sub>d</sub> x A	0.27 x 2.54
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: twin-scroll turbocharger, High Precision
		Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	СС	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		Min. RON 91
Max output	kW/hp	245/333
at	rpm	5500 - 6250
Max torque	Nm	450
at	rpm	1600 - 4800
48V mild hybrid technology		
Max output	kW/hp	8/11
Electrical System	A L /	00/1
12V battery/installation	Ah/-	90 / luggage compartment
48V battery/installation	Ah/-	11 / engine compartment
Driving Dynamics and Safe	ety	
Suspension, front	[	Double-wishbone axle in aluminium construction with separate lower track arm,
		small steering roll radius, transverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
3		Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
		Fading Compensation, Start-Off Assistant; optional: Adaptive suspension,
		Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
		crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS),
		optional: Integral Active Steering
Steering ratio, overall	:1	17.0
Tyres, front/rear		245/50 R18 100Y
Rims, front/rear		8J x 18 light-alloy

			BMW 640i Gran Turismo
Transmission			
Type of transmission	1		Eight-speed Steptronic transmission
Gear ratios	I	:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.136
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	3.077
Performance			
Power-to-weight ratio	o (DIN)	kg/kW	7.6
Output per litre		kW/I	81.7
Acceleration 0-1	100 km/h	S	5.5
Top speed		km/h	250
BMW EfficientDyn	amics		
BMW EfficientDynam	nics		Mild hybrid technology with 48V starter-generator, Brake Energy Regeneratio
standard features			with recuperation display, Auto Start Stop function, ECO PRO and COMFOR
			mode with coasting function, Proactive Driving Assistant, Optimum Shift
			Indicator, Electric Power Steering, BMW EfficientLightweight, optimised
			aerodynamic attributes, active air flap control, on-demand operation
			of ancillary units, map-regulated oil pump, differential with optimised
			warm-up behaviour, tyres with reduced rolling resistance
Fuel Consumption	ECE		
Urban		l/100 km	8.9 - 8.7
Extra-urban		l/100 km	5.9 – 5.7
Combined		l/100 km	7.0 - 6.8
CO <sub>2</sub>		a/km	160 – 155
		3	

Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Height including roof fin
 Oil change

Emission rating

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

# The new BMW 6 Series Gran Turismo. 640i xDrive.

		BMW 640i xDrive Gran Turismo
Deste		
Body		E / E
No of doors/seats Length/width/height <sup>1)</sup>		<u> </u>
(unladen)	mm	50917190271540
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.5
Fuel tank capacity	approx. I	68
Engine oil 2)	approx.1	6.5
Weight, unladen, to DIN/EU	kg	1910 / 1985
Max load to DIN	kg	665
Max permissible weight	kg	2575
Max axle load, front/rear	kg	1240 / 1420
Max trailer load,	kg	
braked (12%)/unbraked		2100 / 750
Max roofload/max towbar	kg	75 / 100
download		
Luggage comp capacity		600 – 1800
Air resistance	c <sub>d</sub> x A	0.27 x 2.54
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: twin-scroll turbocharger, High Precision
		Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable
		camshaft timing
Effective capacity	CC	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		Min. RON 91
Max output	kW/hp	245 / 333
at	rpm	5500 – 6250
Max torque	Nm	450
at	rpm	1600 – 4800
48V mild hybrid technology		
Max output	kW/hp	8/11
Flastainal Constant		
Electrical System	A h /	00//
12V battery/installation	Ah/- Ah/-	90 / luggage compartment
48V battery/installation	An/-	11 / engine compartment
Driving Dynamics and Safe	etv	
Suspension, front		Double-wishbone axle in aluminium construction with separate lower track arm,
		small steering roll radius, transverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air
, ,		suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems	ç	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
		Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
	F	Fading Compensation, Start-Off Assistant, all-wheel-drive system xDrive linked
		with DSC; optional: Adaptive suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
		crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS),
		optional: Integral Active Steering
Steering ratio, overall	:1	16.5
Tyres, front/rear		245/50 R18 100Y
Rims, front/rear		8J x 18 light-alloy

Transmission			
Type of transmi	ssion		Eight-speed Steptronic transmission
Gear ratios		:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.136
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	3.077
Performance			
Power-to-weigh	t ratio (DIN)	kg/kW	7.8
Output per litre	· ·	kW/I	81.7
Acceleration	0–100 km/h	S	5.4
Top speed		km/h	250
BMW Efficient	Dynamics		
BMW EfficientD	ynamics		Mild hybrid technology with 48V starter-generator, Brake Energy Regeneratic
standard feature	25		with recuperation display, Auto Start Stop function, ECO PRO and COMFOR mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive differential with optimised warm-up behaviour, tyres with reduced rolling resistance
Fuel Consum	otion ECE		
Urban	-	l/100 km	9.5 - 9.4
Extra-urban		l/100 km	6.2 - 6.0
Combined		l/100 km	7.4 - 7.2
CO <sub>2</sub>		g/km	170 – 166
Emission rating			Euro 6d

<sup>1)</sup> Height including roof fin <sup>2)</sup> Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

### The new BMW 6 Series Gran Turismo. 620d.

		BMW 620d Gran Turismo
Body		
No of doors/seats		5/5
Length/width/height 1)	mm	5091 / 1902 / 1538
(unladen)		00017100271000
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.3
Fuel tank capacity	approx. I	66
Engine oil 2)		5.5
Weight, unladen, to DIN/EU	kg	1835 / 1910
Max load to DIN	kg	655
Max permissible weight	kg	2490
Max axle load, front/rear	kg	1150 / 1420
Max trailer load,	kg kg	11007 1420
braked (12%)/unbraked	ĸy	2100/750
Max roofload/max towbar	ka	75/100
download	kg	757100
		600 - 1800
Luggage comp capacity Air resistance	Cd X A	0.25 x 2.54
All resistance	CdXA	0.25 X 2.34
Power Unit		
Config/No of cyls/valves		In-line / 4 / 4
Engine technology	E	BMW TwinPower Turbo technology: multi-stage turbocharging, common-rail
		direct injection with solenoid injectors (max. injection pressure: 2500 bar)
Effective capacity	CC	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	140 / 190
at	rpm	4000
Max torque	Nm	400
at	rpm	1750 – 2500
48V mild hybrid technology		
Max output	kW/hp	8/11
Electrical System		
12V battery/installation	Ah/-	90 / luggage compartment
48V battery/installation	An/-	11 / engine compartment
Driving Dynamics and Safe		
Suspension, front	D	ouble-wishbone axle in aluminium construction with separate lower track arm,
		small steering roll radius, transverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air
		suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems	S	tandard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
		Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
		Fading Compensation, Start-Off Assistant; optional: Adaptive suspension,
		Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
		crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS),
		optional: Integral Active Steering
Steering ratio, overall	:1	17.0
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy

			BMW 620d Gran Turismo
Transmission			
Type of transmiss	ion		Eight-speed Steptronic transmission
Gear ratios	1	:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.136
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	3.077
Performance			
Power-to-weight r	atio (DIN)	kg/kW	13.1
Output per litre		kW/I	70.2
	0–100 km/h	S	7.9
Top speed		km/h	220
BMW EfficientD	ynamics		
BMW EfficientDyr standard features	namics		Vild hybrid technology with 48V starter-generator, Brake Energy Regenerativith recuperation display, Auto Start Stop function, ECO PRO and COMFOF mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter
<b>Fuel Consumpti</b> Urban	on ECE	l/100 km	5.1-5.0
Extra-urban		l/100 km	4.2 - 4.1
Combined		l/100 km	4.2 - 4.1
Combined			120 - 116
CO <sub>2</sub>		g/km	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Height including roof fin
 Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

### The new BMW 6 Series Gran Turismo. 630d.

		BMW 630d Gran Turismo
Body		515
No of doors/seats		5/5
Length/width/height 1)	mm	5091/1902/1538
(unladen)		2070
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1649
Ground clearance	mm	138
Turning circle	m	12.3
Fuel tank capacity	approx. I	66
Engine oil 2)		7.0
Weight, unladen, to DIN/EU	kg	1930 / 2005
Max load to DIN	kg	645
Max permissible weight	kg	2575
Max axle load, front/rear	kg	1215 / 1425
Max trailer load,	kg	0400/750
braked (12%)/unbraked		2100/750
Max roofload/max towbar	kg	75/100
download		CO0 1000
Luggage comp capacity		600 - 1800
Air resistance	c <sub>d</sub> x A	0.25 x 2.54
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology	E	BMW TwinPower Turbo technology: multi-stage turbocharging, low-pressure
		turbocharger with variable inlet geometry, common-rail direct injection with
		piezo injectors (max. injection pressure: 2700 bar)
Effective capacity	CC	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	210/286
at	rpm	4000
Max torque	Nm	650
at	rpm	1500 – 2500
48V mild hybrid technology		
Max output	kW/hp	8/11
Electrical System		
12V battery/installation	Ah/-	90 / luggage compartment
48V battery/installation		11 / engine compartment
Driving Dynamics and Safe		
Suspension, front	D	Nouble-wishbone axle in aluminium construction with separate lower track arm, small steering roll radius, transverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air
		suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems	S	tandard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
	0	Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
		Fading Compensation, Start-Off Assistant; optional: Adaptive suspension,
		Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
5 1 1	1	front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
		crash-active front head restraints, crash sensors, tyre pressure indicator
		Electric Power Steering (EPS),
Steering		
Steering		optional: Integral Active Steering
Steering Steering ratio, overall	:1	<b>3</b> ( <i>n</i>
	:1	optional: Integral Active Steering

			BMW 630d Gran Turismo
Transmission			
Type of transmission			Eight-speed Steptronic transmission
Gear ratios	1	:1	5.500
		:1	3.520
		:1	2.200
	IV	:1	1.720
	V	:1	1.317
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.993
Final drive		:1	2.563
Performance			
Power-to-weight ratio (D	N)	kg/kW	9.2
Output per litre		kW/I	70.2
Acceleration 0–100	km/h	S	6.1
Top speed		km/h	250
BMW EfficientDynami	cs		
BMW EfficientDynamics		1	Vild hybrid technology with 48V starter-generator, Brake Energy Regenerati
standard features		N	with recuperation display, Auto Start Stop function, ECO PRO and COMFOI mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter
Fuel Consumption EC	E		
Urban		100 km	6.2 - 6.1
Extra-urban	I/	100 km	4.4 - 4.2
Combined	I/	100 km	5.0 - 4.9
CO <sub>2</sub>		g/km	133 – 128
Emission rating			Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Height including roof fin
 Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

# The new BMW 6 Series Gran Turismo. 630d xDrive.

		BMW 630d xDrive Gran Turismo
Body		
No of doors/seats		5/5
Length/width/height 1)	mm	5091 / 1902 / 1540
(unladen)		30317130271340
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.5
Fuel tank capacity	approx. I	66
Engine oil 2)		7.0
Weight, unladen, to DIN/EU	kg	1990 / 2065
Max load to DIN	kg	650
Max permissible weight	kg	2640
Max axle load, front/rear	kg	1280 / 1445
Max trailer load,	kg	12007 1445
braked (12%)/unbraked	Ng	2100/750
Max roofload/max towbar	ka	75/100
download	kg	737100
Luggage comp capacity		600 – 1800
Air resistance	Cd X A	0.25 x 2.54
All Tesistance	Cd X A	0.23 % 2.34
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology	E	BMW TwinPower Turbo technology: multi-stage turbocharging, low-pressure
		turbocharger with variable inlet geometry, common-rail direct injection with
		piezo injectors (max. injection pressure: 2700 bar)
Effective capacity	CC	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	210/286
at	rpm	4000
Max torque	Nm	650
at	rpm	1500 - 2500
48V mild hybrid technology		
Max output	kW/hp	8/11
Electrical System		
Electrical System 12V battery/installation	Ah/-	90 / luggage compartment
48V battery/installation		11 / engine compartment
	An/-	
Driving Dynamics and Safe		
Suspension, front	D	ouble-wishbone axle in aluminium construction with separate lower track arm, small steering roll radius, transverse force compensation, anti-dive
Suspension rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air
Suspension, rear		suspension with automatic self-levelling
Brakes, front		Vented disc brakes, with four-piston fixed callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems	S	tandard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
	-	Brake Control), DBC (Dynamic Brake Control), Dry Braking function,
	F	ading Compensation, Start-Off Assistant, all-wheel-drive system xDrive linked
		with DSC; optional: Adaptive suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
· · · ·	f	front passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,
		on all seats with belt stopper, belt tensioner and belt force limiter at the front, crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		
Steering		crash-active front head restraints, crash sensors, tyre pressure indicator
		crash-active front head restraints, crash sensors, tyre pressure indicator Electric Power Steering (EPS),
Steering Steering ratio, overall Tyres, front/rear		crash-active front head restraints, crash sensors, tyre pressure indicator Electric Power Steering (EPS), optional: Integral Active Steering

			BMW 630d xDrive Gran Turismo
Transmission			
	!		Field and Otendary's transmission
Type of transmis	ssion	4	Eight-speed Steptronic transmission
Gear ratios	I	:1	5.500
		:1	
	IIIIV	:1 :1	2.200
	V	:1	1.317
	VIVI	:1	1.000
		:1	
	VIII	:1	0.640
<u></u>	R	:1	3.993
Final drive		:1	2.563
Performance			
Power-to-weigh	t ratio (DIN)	kg/kW	9.5
Output per litre		kW/I	70.2
Acceleration	0–100 km/h	S	5.9
Top speed		km/h	250
BMW Efficient	Dynamics		
BMW EfficientD	-	N	Nild hybrid technology with 48V starter-generator, Brake Energy Regeneration
standard feature		V	with recuperation display, Auto Start Stop function, ECO PRO and COMFOR mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converte
<b>Fuel Consump</b> Urban	tion ECE	l/100 km	6.7 - 6.4
Extra-urban		1/100 km	4.6 - 4.4
Combined		l/100 km	5.3 - 5.1
COmbined CO2		a/km	140 – 135
002		y/kill	140 - 135

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof fin
 <sup>2)</sup> Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

# The new BMW 6 Series Gran Turismo. 640d xDrive.

		BMW 640d xDrive Gran Turismo		
Dedu				
Body		E ! E		
No of doors/seats Length/width/height <sup>1)</sup>		<u> </u>		
(unladen)	mm	50917190271540		
Wheelbase	mm	3070		
Track, front/rear		1615 / 1647		
Ground clearance	mm	138		
Turning circle	m	12.5		
	approx. I	66		
Fuel tank capacity Engine oil <sup>2)</sup>		7.0		
	ka	2010 / 2085		
Weight, unladen, to DIN/EU Max load to DIN	kg	675		
	kg			
Max permissible weight	kg	2685		
Max axle load, front/rear	kg	1310 / 1465		
Max trailer load,	kg	0100 / 750		
braked (12%)/unbraked		2100/750		
Max roofload/max towbar	kg	75 / 100		
download		<b>COO</b> 1000		
Luggage comp capacity		600 - 1800		
Air resistance	C <sub>d</sub> x A	0.27 x 2.54		
Power Unit				
Config/No of cyls/valves		In-line / 6 / 4		
Engine technology	B	MW TwinPower Turbo technology: multi-stage turbocharging, high- and low-		
Engine teermology	D	pressure turbochargers with variable intake geometry, common-rail direct		
		injection with piezo injectors (max. injection pressure: 2700 bar)		
Effective capacity	CC	2993		
Stroke/bore	mm	90.0 / 84.0		
Compression ratio	:1	16.5		
Fuel	• 1	Diesel		
	LAN//bp			
Max output	kW/hp	250/340		
at Mautanaua	rpm	4400		
Max torque	Nm	700		
at	rpm	1750 – 2250		
48V mild hybrid technology	LAA//bro	8/11		
Max output	kW/hp	8711		
Electrical System				
12V battery/installation	Ah/–	90 / luggage compartment		
48V battery/installation	Ah/–	11 / engine compartment		
Driving Dynamics and Safe				
Suspension, front	D	ouble-wishbone axle in aluminium construction with separate lower track arm,		
		small steering roll radius, transverse force compensation, anti-dive		
Suspension, rear		Five-link axle in aluminium lightweight construction, dual elastic bearing, air suspension with automatic self-levelling		
Brakes, front		Vented disc brakes, with four-piston fixed callipers		
Brakes, rear		Vented disc brakes, with single-piston floating callipers		
Driving stability systems	S	tandard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering		
Driving stability systems	0	Brake Control), DBC (Dynamic Brake Control), Dry Braking function,		
	F	Fading Compensation, Start-Off Assistant, all-wheel-drive system xDrive linked		
		with DSC; optional: Adaptive suspension, Executive Drive		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and		
earery equipment	f	front passenger, head airbags front and rear, three-point inertia-reel seatbelts		
		on all seats with belt stopper, belt tensioner and belt force limiter at the front,		
	·	crash-active front head restraints, crash sensors, tyre pressure indicator		
Steering		Electric Power Steering (EPS),		
oteening		optional: Integral Active Steering		
Stooring ratio overall	:1	16.5		
Steering ratio, overall	:1	245/50 R18 100Y		
Tyres, front/rear		240/00 K 18 1001		
Rims, front/rear		8J x 18 light-alloy		

			BMW 640d xDrive Gran Turismo
Transmission			
Type of transmissi	ion		Eight-speed Steptronic transmission
Gear ratios	1	:1	5.500
		:1	3.520
		:1	2.200
	IV	:1	1.720
	V	:1	1.317
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.993
Final drive		:1	2.563
Performance			
Power-to-weight r	atio (DIN)	kg/kW	8.0
Output per litre		kW/I	83.5
Acceleration (	0–100 km/h	S	5.3
Top speed		km/h	250
BMW EfficientD	ynamics		
BMW EfficientDyr	amics	Ν	/ild hybrid technology with 48V starter-generator, Brake Energy Regeneration
standard features		v	vith recuperation display, Auto Start Stop function, ECO PRO and COMFOR mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter
<b>Fuel Consumpti</b> Urban	on ECE	l/100 km	6.9 - 6.7
Extra-urban		1/100 km	4.8 - 4.6
Combined		I/100 km	5.6 - 5.4
CO <sub>2</sub>		g/km	147 – 141
<u> </u>		gran	<u> </u>

Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Height including roof fin
 <sup>2)</sup> Oil change

Emission rating

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).